



Inflatable Pipe Plugs / Flow Stoppers : OLS



Type: OLS		40/70		70/150		100/180		100/200		200/400		300/600		500/1000		500/1200	
		Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI
Work Press max.		1,5	22	1,5	22	3,0	44	3,0	44	3,0	44	3,0	44	3,0	44	3,0	44
Article no.		7668007		7668008		7668009		7668001		7668002		7668003		7660154		7660156	
Article no. Nitril		————		————		————		7660162		7660163		7660164		7660165		7660167	
Pipe diameters		Maximum backpressure with water															
mm	Inch	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI
40	1,5	0,9	13														
70	2,7	0,7	10	0,9	13												
100	4			0,8	12	2,2	32	2	29								
150	6			0,7	10	1,2	17	1,6	23								
180	7					0,6	9	1,4	20								
200	8							1,3	19	2	29						
300	12									1,8	25	2	29				
400	16									1,2	13	1,8	26				
500	20											1,6	23	2	29	1,9	28
600	24											0,9	13	1,9	28	1,9	28
700	27													1,8	26	1,8	26
800	32													1,7	23	1,8	26
900	35													1,1	13	1,7	25
1000	40													0,5	6	1,7	25
1200	48															0,8	12

- Above mentioned values are directions in clean and round concrete pipes.
- Maximum backpressure for air testing: 200 mbar in all pipe diameters!