



Flex ODS: Pipe Plug with Flexible Bypass



Type: Flex ODS		100/200		200/400		300/600		500/1000		500/1200	
		Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI
Working press max.		2,0	29	2,0	29	2,0	29	2,0	29	2,0	29
Article no.		7668021	*	7668022	*	7668023	*	7660174	*	7660175	*
		7668031	**	7668032	**	7668033	**	-----		-----	
Pipe diameters		Maximum backpressure with water									
mm	Inch	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI
100	4	1,3	19								
150	6	1	14								
200	8	0,7	10	1,3	19						
300	12			1,1	16	1,3	19				
400	16			0,7	10	1,2	17				
500	20					1	14	1,3	19	1,3	19
600	24					0,6	9	1,2	17	1,2	17
700	27							1,1	16	1,1	16
800	32							1,1	16	1,1	16
900	35							1	14	1,1	16
1000	40							0,6	9	1	14
1200	48									0,5	7

- Above mentioned values are directions in clean and round concrete pipes.
- Maximum backpressure for air testing: 200 mbar in all pipe diameters!
- * With Storz coupling.
- ** Without Storz coupling.