



MEGAPLUG-ODS



Type: ODS Megaplug		1400		1600		2000		2400	
		Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI
Working press max.		1,5	22	1,0	14	1,0	14	1,0	14
Article no.		7660159		7660158		7660161		***	
Pipe diameters		Maximum backpressure with water							
mm	inch	Bar	PSI	Bar	PSI	Bar	PSI	Bar	PSI
500	20	1,5	22						
600	24	1,3	19						
700	27	1,3	19	1	14				
800	32	1,2	17	0,9	13	0,9	13		
900	35	1,2	17	0,8	12	0,9	13		
1000	40	1,1	16	0,8	12	0,8	12		
1200	48	1,1	16	0,7	10	0,8	12	0,9	13
1400	55	0,8	12	0,7	10	0,7	10	0,9	13
1600	63			0,5	7	0,7	10	0,8	12
1800	71					0,6	9	0,7	10
2000	80					0,5	7	0,6	9
2200	87							0,5	7
2400	96							0,5	7

- Above mentioned values are directions in clean and round concrete pipes.
 - Maximum backpressure for air testing: 200 mbar in all pipe diameters!
- These plugs are provided with a safety valve at air-inlet at front side.
 On request we can also deliver the Megaplug in a chemical resistant Nitrile Rubber quality.
 Every Megaplug is tested at the maximum working pressure in the largest pipe diameter of that type.
 *** At request.